

TECHNICAL DATA SHEET

LFAL IP20 / Flex Led

VERSION - 06.07.2018


STANDARD LUMINAIRE

Reference	LFAL
Protection Class	IP20
Lighting Source	Flex Led
Dimensions	13 x 5mm
Standard Length	140 - 540 - 1040 - 1540 - 2040 - 2540mm
Length on measure	on request up to 3040mm
Nb Lighting Unit	60 LED/m
Voltage	24V
Power	4.8 W/m
Connecting Cable	1m standard cable 2x1.5mm ²

APPLICATION: cornices, handrails, stairs, shelves



LFAL / Flex Led



FINISH


Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect


ON REQUEST: LFAL Fixations - FCP



FCP-S (fixed with tape & screw)



FCP (fixed with screw)



ON REQUEST

Fixation	FCP (fixed with screw) FCP-S (fixed with tape & screw)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

ON REQUEST : Connecting plug AF/AMS



LIGHTING SOURCE

Lighting Source	Flex Led
Voltage	24V
Power	4.8W/m
Nb Led	60 LED/m
Nb Pitch	16.8mm
Beam Angle	120°
CRI	>80
Cut-Out	every 100mm
Lifetime	50'000h or 5 years
Working T°	-30°C to +75°C



Color Temperature & Luminous Flux / Meter

CCT	2700K	3000K	4000K
lm/m	129 lm	140 lm	166 lm

CERTIFICAT

