

TECHNICAL DATA SHEET

LLS IP20 / Soffite

VERSION - 30.07.2018

STANDARD LUMINAIRE

Reference	LLS		
Protection Class	IP20		
Lighting Source	Soffite		
Connector	Festoon on B'Light conductor 16mm ²		
Dimensions	13 x 17mm		
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm		
Length on measure	on request up to 3000mm		
Nb Lighting Unit	17 bulbs/m		
Voltage	24V		
Power	3W	5W	10W
	51 W/m	85 W/m	170 W/m

FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Old Gold Aspect

ON REQUEST

Fixation	FCP (fixed with screw) FCP-S (fixed with tape & screw)
Connecting Cable	COS3 - COS4 - COS4a
Connecting Plug	AMS / AF
Dimming Option	Phase 220V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Soffite Standard			Soffite Long Life	
Glass	Clear or Frosted			Clear or Frosted	
Power	3W	5W	10W	5W	10W
Voltage	24V	24V	24V	24V	24V
Beam Angle	360°	360°	360°	360°	360°
Lifetime	1'000h	1'000h	1'000h	3'000h	3'000h

Color Temperature & Luminous Flux / Unit

Lighting Source	Soffite Standard			Soffite Long Life	
Power	3W	5W	10W	5W	10W
CCT	2400K	2500K	2600K	2600K	2700K
Luminous Flux/Unit	20 lm	38 lm	80 lm	50 lm	120 lm


CERTIFICAT



APPLICATION: cornices, handrails, stairs, shelves




LLS / Soffite




ON REQUEST: LLS Fixation



FCP-S (fixed with tape & screw)



FCP (fixed with screw)



ON REQUEST : Connecting Cable

COS3 Power Connector



2x1m conductors of 2.5mm²

COS4 Linear bridging



2x8cm conductors of 2.5mm²

COS4a Corner bridging



1x8cm conductors of 2.5mm²
1x11cm conductors of 2.5mm²

ON REQUEST : Connecting plug AMS/AF

