

TECHNICAL DATA SHEET

LU4CSAL IP67 / Flex Led

VERSION - 30.04.2018

STANDARD LUMINAIRE

Reference	LU4CSAL67
Protection Class	IP67 with Silicone
Lighting Source	Flex Led
Dimensions	29 x 32mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000
Length on measure	on request up to 3000mm
Nb Lighting Unit	60 LED/m
Voltage	24V
Power	4.8 W/m
Connecting Cable	One side: 50cm standard cable 2x0.75mm ²
End Caps	EU4

FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome or Gold Aspect

ON REQUEST

Fixation	FCU (Width: +4mm)
Cover	VRC: Clear Glass / VRM: Opaline Glass VSC: Clear Glass / VSM: Opaline Glass
End Caps	EU4C (For VSC/VSM Cover)
Connecting Plug	AMS / AF or AMS-E / AF-E
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Flex Led
Voltage	24V
Power	4.8W/m
Nb Led	60 LED/m - LED Pitch: 16.8mm
Beam Angle	120°
CRI	>80
Cut-Out	every 100mm
Lifetime	50'000h or 5 years
Working T°	-30°C to +75°C


Color Temperature & Luminous Flux / Meter

CCT	2700K	3000K	4000K
lm/m	390 lm	390 lm	425 lm


CERTIFICAT



LU4CSAL / Flex Led




ON REQUEST: LU4CSAL67 FIXATION




LU4CSAL Cover

LU4CSAL + VRC (or VRM)



LU4CSAL + VSC (or VSM)



On Request: Connecting Plug

AF/AMS



AF-E/AMS-E (IP68)

