

TECHNICAL DATA SHEET

TLFAL IP20 / Aga-Led® Type A

VERSION - 06.05.2016

STANDARD LUMINAIRE

Reference	TLFAL
Protection Class	IP20
Lighting Source	Aga-Led® Type A
Connector	Rigid Loop on B'Light conductor 16mm ²
Dimensions	26 x 28mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	36 LED/m
Voltage	24V
Power	36 W/m
Connecting Cable	1m standard cable 2x1.5mm ²

FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect

ON REQUEST

Fixation	TFCP (Width: +3mm / Ht: +0.2mm) TFCP-S (Width: +3mm / Ht: +4.5mm)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Aga-Led® Type A
Ref	A10
Voltage	24V
Power	1W
Beam Angle	15°
CRI	80
Lifetime	60'000h
Working T°	-30°C ~ +55°C
Option	AGC: Anti Glare Optic



Color Temperature & Luminous Flux / Unit

CCT	2800K	4000K
Luminous Flux/Unit	40 lm	45 lm


CERTIFICAT




APPLICATION: cornices, handrails, stairs, shelves



TLFAL / AGA-LED® TYPE A - Rigid Loop



ON REQUEST: TLFAL Fixation TFCP-S



ON REQUEST : Connecting plug AF/AMS

