

TECHNICAL DATA SHEET

TLFAL IP20 / Aga-Led® Type B

VERSION - 16.12.2016


STANDARD LUMINAIRE

Reference	TLFAL
Protection Class	IP20
Lighting Source	Aga-Led® Type B
Connector	Rigid Loop on B'Light conductor 16mm ²
Dimensions	26 x 21mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	36 LED/m
Voltage	24V
Power	34.56W/m to 43.2 W/m
Connecting Cable	1m standard cable 2x1.5mm ²

APPLICATION: cornices, handrails, stairs, shelves



TLFAL / AGA-LED® TYPE B - Rigid Loop



FINISH


Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling
	Powder Coating RAL
	Color Anodising
	Polished Aluminium Chrome Aspect
	Polished Aluminium Gold Aspect

ON REQUEST

Fixation	TFCP (Width: +3mm / Ht: +0.2mm)
	TFCP-S (Width: +3mm / Ht: +4.5mm)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX
	Ask technical departement for more information

ON REQUEST: TLFAL Fixation TFCP-S



ON REQUEST : Connecting plug AF/AMS



LIGHTING SOURCE

Lighting Source	Aga-Led® Type B - Generation 2	
Ref	B3	B6
Power	0.96W	1.2W
Voltage	24V	24V
Beam Angle	120°	120°
CRI	80	80
Lifetime	50'000h	
Working T°	-20°C to +45°C	
Environmental protection	Modified acrylate resin	

Color Temperature & Luminous Flux / Unit

	2200K	2400K	2700K	3000K	4000K
Aga-Led® B3-G2	- -	97 lm	137lm	137lm	137lm
Aga-Led® B6-G2	129 lm	140 lm	166 lm	166 lm	166 lm

CERTIFICAT

