

TECHNICAL DATA SHEET

Ceiling Linear Lighting / LU6AL-LPS / Aga-Led® Type B

VERSION - 14.06.2018

STANDARD LUMINAIRE

| | |
|--------------------|---|
| Reference | LU6AL-LPS |
| Protection Class | IP20 |
| Lighting Source | Aga-Led® Type B |
| Connector | Rigid Loop on B'Light conductor 16mm ² |
| Dimensions - mm | 40 x Ht.380 <i>Power Supply Profil: 40x35x410mm</i> |
| Lenght Standard | 1200mm |
| Lenght on measure | up to 4500mm <i>Ask technical departement for more information</i> |
| Nb Lighting Source | 5 LED/m |
| Voltage | 220V - Power Supply Included |
| Power | 17.5W/m |
| Dimmable | Yes, 1-10V or Dali |
| Grid | Honeycomb |
| End Caps | ERPS |

APPLICATION : CEILING



FINISH

Color Finishing Profil

| | |
|-------------------|--|
| Standard | Natural Anodised Aluminium |
| <i>On request</i> | <i>Thermo-enameling</i> <i>Powder Coating RAL</i> <i>Color Anodising</i> <i>Polished Aluminium Chrome Aspect</i> <i>Polished Aluminium Gold Aspect</i> |

ON REQUEST

| | |
|----------------|---|
| Dimming Option | 1-10V, Dali, KNX <i>Ask technical departement for more information</i> |
|----------------|---|

LIGHTING SOURCE

| | |
|-----------------|-------------------------------------|
| Lighting Source | Aga-Led® 01LP12 |
| Power | 3.5W |
| Voltage | 12V (Dimming) 24V (Non Dimmable) |
| Beam Angle | 16° |
| CRI | 80 |
| Lifetime | 50'000h |
| Working T° | -20°C to +40°C |



Color Temperature & Luminous Flux / Unit

| | | |
|------------------------|--------------|--------------|
| | 2200K | 4000K |
| Aga-Led® 01LP12 | 115 lm | 183 lm |

CERTIFICAT

