

## TECHNICAL DATA SHEET

### LFAL IP20 / Flex Led


VERSION - 06.07.2017

#### STANDARD LUMINAIRE

Reference	LFAL
Protection Class	IP20
Lighting Source	Flex Led
Dimensions	13 x 5mm
Standard Length	140 - 540 - 1040 - 1540 - 2040 - 2540mm
Length on measure	on request up to 3040mm
Nb Lighting Unit	60 LED/m
Voltage	24V
Power	4.8 W/m
Connecting Cable	1m standard cable 2x1.5mm <sup>2</sup>

#### APPLICATION: cornices, handrails, stairs, shelves


##### LFAL / Flex Led




##### ON REQUEST: LFAL Fixation



##### FCP-S (fixed with tape & screw)



##### FCP (fixed with screw)



#### FINISH

##### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling
	Powder Coating RAL
	Color Anodising
	Polished Aluminium Chrome Aspect
	Polished Aluminium Gold Aspect

##### ON REQUEST : Connecting plug AF/AMS



#### ON REQUEST

Fixation	FCP (fixed with screw) FCP-S (fixed with tape & screw)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

#### LIGHTING SOURCE

Lighting Source	Flex Led
Voltage	24V
Power	4.8W/m
Nb Led	60 LED/m - LED Pitch: 16.8mm
Beam Angle	120°
CRI	>80
Cut-Out	every 100mm
Lifetime	50'000h or 5 years
Working T°	-30°C to +75°C

#### Color Temperature & Luminous Flux / Meter

<b>CCT</b>	<b>2700K</b>	<b>3000K</b>	<b>4000K</b>
<b>lm/m</b>	129 lm	140 lm	166 lm

#### CERTIFICAT



#### AGABEKOV



**AGABEKOV SA Manufacture** 6, ROUTE DE COMPOIS  
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND  
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08  
E - mail: info@agabekov.com



**AGABEKOV SA Bureau d'etudes** 6, ROUTE DE COMPOIS  
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND  
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08  
Internet: www.agabekov.com

