

## TECHNICAL DATA SHEET

### LFX-AC IP20 / Xenon

VERSION - 21.03.2016

#### STANDARD LUMINAIRE

Reference	LFX-AC			
Protection Class	IP20			
Lighting Source	Xenon			
Connector	Rigid Loop on B'Light conductor 16mm <sup>2</sup>			
Dimensions	13 x 23mm			
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm			
Length on measure	on request up to 3000mm			
Nb Lighting Unit	18 bulbs/m			
Voltage	24V			
Power	3W	5W	8.5W	10W
	54 W/m	90 W/m	153 W/m	180 W/m

#### FINISH

##### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Old Gold Aspect

#### ON REQUEST

Fixation	BFA (Width: +12mm) FCP-S (Width: +2mm / Ht: +3mm)
Connecting Cable	COS3 - COS4 - COS4a
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

#### LIGHTING SOURCE

Lighting Source	Xenon Long Life			
Glass	Clear or Frosted			
Power	3W	5W	8.5W	10W
Voltage	24V	24V	24V	24V
Beam Angle	360°	360°	360°	360°
Color Temperature	2300K	2400K	2600K	2500K
Light Output lm/unit	12.6lm	40lm	95lm	90lm
Lifetime	20'000h	20'000h	10'000h	20'000h


#### CERTIFICAT




#### APPLICATION: cornices, handrails, stairs, shelves





##### LFX-AC / XENON - Rigid Loop



##### LFX-AC + FCP-S




##### LFX-AC + BFA




#### ON REQUEST : Connecting Cable

##### COS3 Power Connector



2x1m conductors of 2.5mm<sup>2</sup>

##### COS4 Linear bridging



2x8cm conductors of 2.5mm<sup>2</sup>

##### COS4a Corner bridging



1x8cm conductors of 2.5mm<sup>2</sup>  
1x11cm conductors of 2.5mm<sup>2</sup>

#### ON REQUEST : Connecting plug AMS/AF

