

TECHNICAL DATA SHEET

LLS IP20 / Soffite

VERSION - 16.03.2016

STANDARD LUMINAIRE

Reference	LLS		
Protection Class	IP20		
Lighting Source	Soffite		
Connector	Festoon on B'Light conductor 16mm ²		
Dimensions	13 x 21mm		
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm		
Length on measure	on request up to 3000mm		
Nb Lighting Unit	17 bulbs/m		
Voltage	24V		
Power	Xenon 3W	Xenon 5W	Xenon 10W
	51 W/m	85 W/m	170 W/m

FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Polished Aluminium Old Gold Aspect

ON REQUEST

Fixation	BFA (Width: +12mm) FCP-S (Width: +2mm / Ht: +3mm)
Connecting Cable	COS3 - COS4 - COS4a
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Soffite Standard			Soffite Long Life	
	Clear or Frosted			Clear or Frosted	
Glass					
Power	3W	5W	10W	5W	10W
Voltage	24V	24V	24V	24V	24V
Beam Angle	360°	360°	360°	360°	360°
Color Temperature	2400K	2500K	2600K	2600K	2700K
Light Output lm/unit	20lm	38lm	80lm	50lm	120lm
Lifetime	1'000h	1'000h	1'000h	3'000h	3'000h


CERTIFICAT




APPLICATION: cornices, handrails, stairs, shelves





LLS / XENON - Festoon



LLS + FCP-S




LLS + BFA




ON REQUEST : Connecting Cable

COS3 Power Connector



2x1m conductors of 2.5mm²

COS4 Linear bridging



2x8cm conductors of 2.5mm²

COS4a Corner bridging



1x8cm conductors of 2.5mm²
1x11cm conductors of 2.5mm²

ON REQUEST : Connecting plug AMS/AF

