

TECHNICAL DATA SHEET

LU4CX IP20 / Xenon

VERSION - 28.04.2016

STANDARD LUMINAIRE

Reference	LU4CX			
Protection Class	IP20			
Lighting Source	Xenon			
Connector	Rigid Loop on B'Light conductor 16mm ²			
Dimensions	29 x 32mm			
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm			
Length on measure	on request up to 3000mm			
Nb Lighting Unit	17 bulbs/m			
Voltage	24V			
Power	3W	5W	8.5W	10W
	51 W/m	85 W/m	144.5 W/m	170 W/m
Connecting Cable	1m standard cable 2x2.5mm ²			

FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Old Gold Aspect

ON REQUEST

Fixation	FCU (Width: +4mm)
Reflector	RIP
Cover	VRC (Clear Glass) / VRM (Opaline Glass) VSC (Clear Glass) / VSM (Opaline Glass)
End Caps	EU4 EU4C (For VSC/VSM Cover)
Connecting Plug	AMS / AF
Dimming Option	Phase 220V, Dali, KNX <i>Ask technical departement for more information</i>


LIGHTING SOURCE

Lighting Source	Xenon Long Life			
Glass	Clear or Frosted			
Power	3W	5W	8.5W	10W
Voltage	24V	24V	24V	24V
Beam Angle	360°	360°	360°	360°
Color Temperature	2300K	2400K	2600K	2500K
Light Output lm/unit	12.6lm	40lm	95lm	90lm
Lifetime	20'000h	20'000h	10'000h	20'000h


CERTIFICAT




APPLICATION: Cornices, Stairs, Shelves



LU4CX / Xenon - Rigid Loop





ON REQUEST: LU4CX Fixation FCU



ON REQUEST: LU4CX Cover

VRC (or VRM)
Xenon 5W max.


VSC (or VSM)
Xenon 5W max.



ON REQUEST: LU4X End Caps

EU4

EU4C



ON REQUEST : Connecting plug AF/AMS

