

TECHNICAL DATA SHEET


LU4X IP20 / Xenon

VERSION - 27.04.2016


STANDARD LUMINAIRE

Reference	LU4X			
Protection Class	IP20			
Lighting Source	Xenon			
Connector	Rigid Loop on B'Light conductor 16mm ²			
Dimensions	24 x 21mm			
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm			
Length on measure	on request up to 3000mm			
Nb Lighting Unit	17 bulbs/m			
Voltage	24V			
Power	3W	5W	8.5W	10W
	51 W/m	85 W/m	144.5 W/m	170 W/m
Connecting Cable	1m standard cable 2x2.5mm ²			

APPLICATION: Cornices, Windows, Balustrades



LU4X / Xenon - Rigid Loop




FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Old Gold Aspect

ON REQUEST: LU4X Fixation FCU





ON REQUEST

Fixation	FCU (Width: +4mm)
Reflector	RIP
Cover	VRC (Clear Glass) / VRM (Opaline Glass) VSC (Clear Glass) / VSM (Opaline Glass)
End Caps	EU4 EU4C (For VSC/VSM Cover)
Connecting Plug	AMS / AF
Dimming Option	Phase 220V, Dali, KNX <i>Ask technical departement for more information</i>

ON REQUEST: LU4X Cover

VRC (or VRM)
Xenon 5W max.

VSC (or VSM)
Xenon 5W max.



LIGHTING SOURCE

Lighting Source	Xenon Long Life			
Glass	Clear or Frosted			
Power	3W	5W	8.5W	10W
Voltage	24V	24V	24V	24V
Beam Angle	360°	360°	360°	360°
Color Temperature	2300K	2400K	2600K	2500K
Light Output lm/unit	12.6lm	40lm	95lm	90lm
Lifetime	20'000h	20'000h	10'000h	20'000h

ON REQUEST: LU4X End Caps

EU4

EU4C



CERTIFICAT



ON REQUEST : Connecting plug AF/AMS

