

TECHNICAL DATA SHEET

LU4CSAL IP20 / Aga-Led® Type B

VERSION - 02.09.0215

STANDARD LUMINAIRE

Reference	LU4CSAL
Protection Class	IP20
Lighting Source	Aga-Led® Type B
Connector	Festoon on B'Light conductor 16mm ²
Dimensions	24 x 32mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	18 LED/m
Voltage	24V
Power	21.60 W/m
Connecting Cable	1m standard cable 2x1.5mm ²

FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome or Gold Aspect

ON REQUEST

Fixation	FCU (Width: +4mm)
Cover	VRC: Clear Glass / VRM: Opaline Glass VSC: Clear Glass / VSM: Opaline Glass
End Caps	EU4 EU4C (For VSC/VSM Cover)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Aga-Led® Type B - Generation 2				
Ref	B2	B3	B4	B6	
Voltage	24V	24V	24V	24V	
Power	1.2W	0.96W	1.2W	1.2W	
Beam Angle	120°	120°	120°	120°	
CRI	80	80	80	80	
Color Temperature	lm/Unit				
	2000K	40 ~ 68	40 ~ 82	46 ~ 78	70 ~ 118
	2400K	48 ~ 81	58 ~ 97	55 ~ 93	83 ~ 140
	2800K	68 ~ 114	82 ~ 137	66 ~ 111	99 ~ 166
	4000K	68 ~ 114	82 ~ 137	66 ~ 111	99 ~ 166
Lifetime / L70 at 25°	50'000h / 36'000h				
Working T°	-20°C to +45°C				
Environmental protection	Modified acrylate resin				


CERTIFICAT




APPLICATION: Cornices, Windows, Balustrades



LU4CSAL / AGA-LED® TYPE B - Festoon





LU4CSAL + FCU



LU4CSAL Cover

LU4CSAL + VRC (or VRM)

LU4CSAL + VSC (or VSM)



LU4SAL End Caps

EU4



EU4C

