

TECHNICAL DATA SHEET

LU6AL Pendant / Aga-Led® Type B

VERSION - 19.09.2017

STANDARD LUMINAIRE

Reference	LU6AL
Protection Class	IP40
Lighting Source	Aga-Led® Type B
Connector	Rigid Loop
Size - mm	36 x 59mm without fixture
Lenght on measure	210mm to 3000mm
Nb Lighting Source	17 LED/m
Voltage	24V
Power	16.32 W/m to 20.4 W/m
Dimmable	Yes
Cover	VSM6 (Opaline Glass)
End Caps	ERPS-N
Fixture	number to be defined according the lenght Standard : 20cm height from ceiling to luminaire

APPLICATION : WALL, CEILING OR FLOOR



FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminuim
On request	<i>Thermo-enameling</i> <i>Power Coating RAL</i> <i>Color Anodising</i> <i>Chromuin or Gold plating</i>

ON REQUEST

Fixture	Number to define - Height on measure
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Aga-Led® Type B - Generation 2	
Ref	B3	B6
Power	0.96W	1.2W
Voltage	24V	24V
Beam Angle	120°	120°
CRI	80	80
Lifetime	50'000h	
Working T°	-20°C to +45°C	
Environmental protection	Modified acrylate resin	

Color Temperature & Luminous Flux / Unit

	2200K	2400K	2700K	3000K	4000K
Aga-Led® B3-G2	--	97 lm	137lm	137lm	137lm
Aga-Led® B6-G2	129 lm	140 lm	166 lm	166 lm	166 lm

CERTIFICAT

